



## CyberBase™

Tactical Secure 5G Base Station  
Built For Resilience. Engineered For The Mission.

CODE  
SA5G-2001

## SECURE. SCALABLE. MISSION-READY.

### PRODUCT OVERVIEW

CyberBase™ is a ruggedized 5G gNodeB Base Station built for tactical military communications. It delivers secure, high-speed connectivity for mission-critical applications including command and control, surveillance, and situational awareness.

With ultra-low latency and modular architecture, CyberBase™ enables resilient 5G networking across forward-deployed units, ships, and mobile operations.

It also serves as a trusted edge node for mission networks in contested or disconnected environments.

### KEY FEATURES

- **Ruggedized Design:** Resists extreme temperatures, shock, and vibration.
- **High-Speed 5G Connectivity:** Supports low latency (<1ms) and high data rates for real-time operations.
- **Modular Architecture:** Integrates seamlessly with existing military networks and supports future scalability.
- **Electromagnetic Resilience:** Resistant to EMI and jamming in contested environments.
- **Scalable Network Support:** Enables flexible deployment for multiple users and edge nodes.
- **Backhaul Integration:** Connects via RJ45 to SATCOM terminals or fiber for land/maritime flexibility.
- **Trusted Edge Support:** Enables secure operation in contested or disconnected mission environments.

### APPLICATIONS

Ideal for secure communications, battlefield coordination, ISR data feeds, logistics, disaster response, and forward base connectivity.

Supports ship-to-shore and ship-to-ship networks, enables encrypted tactical data sharing, and integrates with SATCOM or fiber backhaul for versatile deployment across maritime and terrestrial domains. Also supports mission networks operating in contested or disconnected environments.



## MINI SPECIFICATION

Requirement	Specification
Frequency Bands Supported	Tactical: N79 Public: N34, N38, N40, N41, N46, N47, N48, N50, N51, N53, N54, N77, N78, N90, N101
Coverage Range	2–4km (environment dependent)
MIMO Configuration	2x2 MIMO
Throughput	100Mb/s to 1Gb/s
CyberSecurity	AES–256 (PQC Planned)
Ruggedization	Ruggedized Enclosure Option



## APPLICATIONS

- Real–Time Command and Control
- Situational Awareness
- Tactical Data Sharing
- Secure Communications
- Logistics and Supply Chain Management
- Disaster Response and Recovery
- Contested and Disconnected Environments
- Forward Operating Base (FOB) Connectivity

## Requirement Specification

Requirement	Specification
Channel Bandwidth	Up to 50 MHz
Latency	<1 ms (Low Latency Modes)
EMI Protection	Resistant to EMI and jamming
Backhaul Data Connector	RJ45 Ethernet
Power Consumption	175W
Supply Voltage	24–48V
Mass	28lbs (12.7kg)
Dimensions (Radio Unit)	9 x 13.5 x 20.5" (22.8 x 34.3 x 52cm)

Information furnished by Assured Space is believed to be accurate and reliable. However, no responsibility is assumed by Assured Space for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Assured Space. Trademarks and registered trademarks are the property of their respective owners.

[www.assuredspace.com](http://www.assuredspace.com)

3200 N. Dobson Rd., Chandler, AZ 85224 • 602–363–8425

